

# Modelo: QR35

1-3/4 HP, 1 Fase, 220-240V~50/60 Hz

Modelo	QR35
HorsePower (H.P)	1-3/4
Refrigerante	R404A
Desplazamiento	34.45
Power Source	208-220V ~ 50/ 60HZ
Nominal Capacity	6036
COP	2.58
Ruido (SPL)	≤64
Cross Reference	CAJ4519

CONDENSING TEMP °C	Temperatura de evaporación							
	-25°C	-20°C	-15°C	-10°C	-5°C	0°C	7.2°C	15°C
54.4			1868	2496	3221	4075	5632	7717
45°C	1274	1841	2481	3230	4105	5133	6943	9447

Compresor hermético de pistón 1.5–1.8 HP  
con conexión de cobre

Parámetro de aplicación	
Motorinput	2100
RLA	9.7
LRA	45
Nivel de aislamiento	F
Revoluciones	2860
Resistencia del bobinado de arranque (25°C)	5.97
Resistencia del bobinado de marcha (25°C)	1.39
Capacitor de Arranque	100µF
Capacitor de marcha	35µF
Start potential relay	HLR3800-4G3D
Carga de aceite refrigerante	500
Grado del aceite refrigerante	EMKARATE RL32H

## Dimensiones

